

CHAIN S

100% SYNTHETIC LUBRICANT FOR MULTIPLE CHAINS AND ORGANS

500002/05.17

Rev. 3

DESCRIPTION & APPLICATIONS

CHAIN S is a fully synthetic lubricant and polyvalent preservative.

CHAIN S is used in industry, mechanical workshops, garages, repair shops for motorcycles and bicycles, household and do-it-yourself workshop. It is particularly suited for easy and easy lubrication of chains, hinges, bolts, springs, locks, articulated joints, Bowden cables, battery terminals, slides, small gears, etc.

ADVANTAGES

- Very good penetration.
- Great adhesion.
- Resistance to high pressures and temperatures
- Resistance to splashing water.
- Corrosion resistance.
- Prevents chain lengthening by wear.

PACKAGING

- Available in white metal sprays of 500 ML.
- Double ball valve for multi-position use.
- Delivered with 2 spray nozzles : 1 short and 1 long (100mm)

ENVIRONMENT, HEALTH & SAFETY

Inflammable ! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal.
Throw away only if completely empty.
Keep out reach of children.

Propulsion gas (propane-butane) with no ozone depletion potential.

Shelf date: 3 years.

CHAIN S

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	995
Appearance	-	-	clair
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	320
Flash point	°C	NFT 60118	240
Application temperature	°C	-	-40 à 200

The average values are given for information only and ...