

CONTACT

OILS FOR CHAIN-SAW CHAINS

230021-230022-230064-230196-230550/08.10

Rev. 0

DESCRIPTION & APPLICATIONS

CONTACT are mineral chain oils for chain saws, they are reinforced with a polymer adhesive in order to obtain a strong oil film. This type of oil is also provided for hammers and transmission chains with loss lubrication.

The qualities CONTACT M (edium), CONTACT H (eavy) CONTACT J, CONTACT S (uper Heavy) are for the chain saws with internal combustion engine.

CONTACT E was specifically developed for the lubrication of electric saws.

ADVANTAGES

- Strong adhesion.
- Lubricity.
- Choice of viscosity.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA				
			J	Type E	Type H	Type M	Type S
Type	-	-	J	Type E	Type H	Type M	Type S
SAE grade	-	-	50	20	40	30	140
ISO VG	-	-	220	46	150	100	460
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	220	52	160	110	460
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	19	7	15	11	33
Flash point	°C	NFT 60118	255	232	235	244	340
Product number	-	-	230550	230064	230022	230021	230196

The average values are given for information only.