

# GERION LE

100% SYNTHETIC LUBRICANT  
FOR EXTENDED OIL CHANGE INTERVALS

210051/07.18

Rev. 9

## DESCRIPTION & APPLICATIONS

GERION LE 75W80 has been designed to lubricate all manual gearboxes demanding an extreme-pressure level of performance API GL4 and a SAE grade of 75W80, particularly for gearboxes requiring ZF TE-ML 02 D approval (extended oil change interval up to 540.000 km).

## ADVANTAGES

- Increased extreme-pressure properties that guarantee good protection of the gear system.
- Excellent fluidity at low temperatures to facilitate gear change from vehicle start up, even in the coldest conditions.
- Compatibility with non-ferrous metals.

## PERFORMANCES

Satisfies to the following specifications:

API GL4

DAF

IVECO

MAN 341 Type E-3/Z-3/Z-5

RENAULT

Volvo 97305/97307

ZF-TE-ML 02E

ZF-TE ML 01E/16P

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# GERION LE

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W80
Specific gravity at 15°C	kg/m <sup>3</sup>	NFT 60101	857
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	55
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	9,2
Viscosity index	-	NFT 60136	150
Flash point	°C	NFT 60118	>200
Pour point	°C	NFT 60105	-48

*The average values are given for information only.*