

MATIC ATF

FLUID FOR AUTOMATIC GEAR-BOXES

210030/11.17

Rev. 1

DESCRIPTION & APPLICATIONS

MATIC ATF is a Type A Suffix A hydraulic fluid specially created for the lubrication of the clutches and the automatic or semi-automatic gear-boxes of cars, engines, industrial and commercial vehicles, etc.

MATIC ATF is recommended for the lubrication of all automatic transmissions with couplers converters for which the constructor recommends the use of a fluid meeting the Type A Suffix A performance.

ADVANTAGES

- High viscosity index which is stable at service
- Excellent resistance to oxidation
- Rapid desemulsion.

PERFORMANCES

Satisfies to the following specifications:

GM ATF TypeA Suffix A

MB 236,2

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

MATIC ATF

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	870
Colour / Saybolt	-	ASTM D 156	red
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	38
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	7
Viscosity index	-	NFT 60136	164
Flash point	°C	NFT 60118	214
Pour point	°C	NFT 60105	-45
Product number	208 L	-	210030

The average values are given for information only.