BD-30 · 230 VAC · 12 or 24 VDC
DIAPHRAGM PUMP for AdBlue®

TECHNICAL CARD

G 258

30 l/min

230 VAC

0.37 kW



mm (approx.) 180 / 280 / 180

kg 6

BD-30 230 VAC	02231-CF00000

30 l/min

12/24 VDC

0.18 kW



mm (approx.) 180 / 280 / 180

kg 5

BD-30 12 VDC BD-30 24 VDC	02240 022400100

USE:

- Self-priming diaphragm pump for AdBlue/DEF
- It is made of compatible materials with this type of fluid in order to avoid damages both the liquid and the parts that are in touch with it.

TECHNICAL FEATURES

- Flow: 30 l/min
- Motor: 0.37 kW 230 VAC · 50/60 Hz single-phase · self-ventilated
  0.18 kW 12 or 24 VDC
- Consumption: 0.7 A (230 VAC)
  12 A (12 VDC)
  7.3 A (24 VDC)
- 1750 rpm
- S2 20' duty
- IP-55 protection
- Min./max. Temperature: -5 ºC / +40 ºC
- Pressure: 1.6 bar
- Inlet/outlet: F3/4"
- ON/OFF Switch
- 2 m electric cable with approved plug (230 VAC)