OIL NEK







estremità flessibile - flexible end



estremità rigida - stiff end

IT. Kit pistola e contalitri

Pistola per travaso olio con contalitri elettronico integrato . Il contalitri ad ingranaggi ovali OIL FLOW, può essere integrato con la pistola OIL NEK in modo da ottenere uno strumento maneggevole ed ergonomico estremamente efficace nel controllo e nella gestione dell'erogazione dell'olio. Il design innovativo permette una facile ispezione/manutenzione, e nel contempo l'estrema solidità del corpo contalitri in alluminio pressofuso conferisce resistenza alle alte pressioni.

Caratteristiche

- parziale 5 cifre
- totale 7 cifre
- portata fino a 30l/min
- entrata/uscita 1/2" F BSP-G
- precisione ± 0,5 %
- ripetibilità 0,2 %
- pressione max 70 Bar
- fluidi olio (viscosità max 2000 cSt)

EN. Nozzle and meter kit

Oil transfer nozzle with integrated electronic flow meter. The oval gear flow meter OIL FLOW, can be integrated with the OIL NEK nozzle in order to obtain a manageable and ergonomic instrument that is extremely effective in the control and management of the oil supply. The innovative design allows easy inspection / maintenance, and at the same time the extreme solidity of the die-cast aluminum flow meter body confers resistance to high pressures

Features

- *partial 5 digits*
- *total 7 digits*
- *flow rate up to 30l/min*
- *inlet/outlet 1/2" F BSP-G*
- *precision ± 0,5 %*
- *repeatability 0,2 %*
- *pression max 70 Bar*
- *fluids oil (max viscosity 2000 cSt)*

Ref.	Model			Uscita Outlet	fluido fluid	LxWxH(mm)	Kg	N° boxes europallet	N° boxes europallet
ONS10R	OIL NEK estremità rigida	-	-	1/2" F	olio - oil	300X160X110	1,0	180	180
ONS11R	OIL NEK estremità rigida+OILFLOW	2xAAA	•	1/2" F	olio - oil	300X160X110	1,5	180	180
ONS10F	OIL NEK estremità flessibile	-	-	1/2" F	olio - oil	300X160X110	1,0	180	180
ONS11F	OIL NEK estremità flessibile+OILFLOW	2xAAA	•	1/2" F	olio - oil	300X160X110	1,5	180	180