

MATIC DX III

AUTOMATIC TRANSMISSION FLUID WITH DEXRON III-G LEVEL.

210038/09.14

Rev. 3

DESCRIPTION & APPLICATIONS

Matic DX III is an ATF (Automatic Transmission Fluid), Dexron III-G.

This mineral based oil contains additives to provide excellent friction properties, a strong anti-oxidative ability (against cooler-corrosion), a perfect fluidity at very low temperatures and an unchanged behavior and quality at high temperatures.

Matic DX III is ideal for use in:

- automatic gearboxes
- power shift transmissions
- couplings and torque converters
- power steering
- hydrostatic transmissions

ADVANTAGES

- The ideal ATF where DEXRON III is required.
- Perfectly compatible with seals, ferrous and non-ferrous metals.
- Can also be used as hydraulic fluid, type HV, viscosity ISO VG 32.

PERFORMANCES

Satisfies to the following specifications:

ALLISON C4

CAT TO2

DENISON HF0

Ford MERCON M931004

GM ATF DEXRON III G

MB 236.1/236.5/236.6/236.7

VOITH 55.6335

ZF-TE ML 03D

ZF-TE-ML 04D/09/11A/11B

ZF-TE ML 17C

MATIC DX III

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	862
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	35,8
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	8
Viscosity index	-	NFT 60136	200
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	18000
Flash point	°C	NFT 60118	176
Pour point	°C	NFT 60105	-48
Colour / Saybolt	-	ASTM D 156	red
Product number	208 L	-	210038

The average values are given for information only.