

# MATIC LT

SYNTHETIC LONG LIFE FLUID FOR AUTOMATIC GEAR-BOXES

210033/01.20

Rev. 8

## DESCRIPTION & APPLICATIONS

MATIC LT is used in all automatic transmissions and hydraulic circuits for cars, buses, industrial and commercial vehicles.

MATIC LT is also suitable for power steering and can also be used as an HV hydraulic fluid ISO VG 32.

MATIC LT is not suitable for continuously variable transmissions (CVT)

## ADVANTAGES

- Long life fluid thanks to the excellent resistance to oxidation
- Recommended for the lubrication of A LARGE NUMBER of automatic transmissions.
- Good friction properties

# MATIC LT

## PERFORMANCES

Satisfies to the following specifications:

AISIN WARNER JWS 3309

ALLISON C4

ALLISON TES 295

BMW/MINI P/N 81 22 9 400 272/275/858/859

BMW/MINI P/N 83 22 0 024 359/0 026 922/0 402 413/0 403 248/0 403 249/7 542 290/9 407 765/9 407 807

CHRYSLER MOPAR ATF +/+2/+3/+4 / AS68RC ATF / SP-III

ESSO LT 71141

Ford M2C-166H/M2C-202B

Ford MERCON V

Ford P/N XT-2-QDX/XT-2-QSM/XT-5-QM/XT-8-QAW/XT-9-QMM5

Ford WSS-M2C922-A1

GM DEXRON III H

GM P/N 19 40 700/19 40 767/21005966 Transaxle/22717466/88900925/9986195/T-IV/Type A suffix A

HONDA Z1 (excl. CVT)

HYUNDAI/KIA ATF Red-1K/Genuine ATF/JWS-3309 T-4/ P/N UM040 CH20 Red-1

IDEMITSU ATF HP

IDEMITSU K 17

ISUZU ATF II/III

ISUZU Genuine ATF

ISUZU P/N 08200-9001

JAGUAR JLM 20238/20292/21044

JAGUAR K17/WSS-M2C922-A1

JASO 1A

JWS 3309

MAN 339 type V1, Z1, Z2

MAN 339 type A/D/F

MAZDA F- 1

MAZDA JWS3317

MAZDA-ATF M-V

MAZDA M-III

MAZDA type T-IV

MB 236.3/236.5/236.6/236.7/236.8/236.81/236.9/236.91/236.10/236.11

Mobil ATF 3309

MITSUBISHI ATF J2

MITSUBISHI SP, P/N MS991156

MITSUBISHI / HYUNDAI /KIA SP-II & SP-III

NISSAN 402

NISSAN MATIC D/J/K/W

## MATIC LT

PORSCHE P/N 000 043 204 41  
PORSCHE P/N 000 043 205 09/28  
PORSCHE P/N 999 917 547 00 (A2)  
PSA Peugeot Citroën P/N Z 000169756  
Renault Matic D2  
SAAB 3309-T-IV  
SHELL LA 2634  
Shell 3403-M115/M-1375.4  
SSANG YONG DSIH 5M-66  
SUBARU Plus ATF HP  
SUBARU P/N K0140Y0700  
SUZUKI 3314/3317  
TEXACO ETL 7045E / ETL 8072B / N402  
TOYOTA type D-II/T/T-III/T-IV  
VOITH 55.6335  
Voith Svc Bltn # 013/118  
VOLVO P/N 1161521/1161540/1161640  
VOLVO 97341/97342  
VW G 052 025/162/990  
VW G US 000 162  
ZF-TE-ML 03D/04D/11A/11B/14A/14B/14C/16L  
ZF-TE ML 17C

### **ENVIRONMENT, HEALTH & SAFETY**

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# MATIC LT

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m <sup>3</sup>	NFT 60101	852
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	33,5
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	7,5
Viscosity index	-	NFT 60136	181
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	11200
Flash point	°C	NFT 60118	211
Pour point	°C	NFT 60105	-54

*The average values are given for information only.*